

ATRUMP MACHINERY, INC.

670 Union Ave. Pomona, CA 91768 Tel: 909-623-6887 Fax: (909) 623-2287 Toll Free Tel: 877-4 ATRUMP

URL:www.atrump.com. e-mail:atrump@atrump.com

Manual Knee Mill MODEL: 3VHG with free D.R.O & Feed

MACHINE FEATURES

- 3HP Spindle Motor, R8 Spindle Taper
- 4,200 rpm spindle speed with HI-LO gear
- Hardened & Ground with turcite-B coating guide way
- C7 Double nut precision acme lead screws for high accuracy and long lasting
- FC30 Meehanite Casting main frame with annealed & stress relieved for long term reliability
- Anti rust chrome quill
- Standard way covers on all three axes
- Tool box & Tools
- Precision APEC class7 spindle bearing to ensure spindle run out within 0.0002
- One shot lubrication system
- Built-in Quartz work light
- Machine finished in Taiwan with China casting



Specification:

Table: Longitudinal travel (X-axis): Cross travel: Z axis quill travel: Knee travel (manual): Quill diameter: Spindle nose to table top (D): Load capacity: Spindle taper: Spindle Speed (r.p.m.): Transmission of spindle & motor: Spindle center to column front surface: Ram Travel:

Head:

Swivel (left/right) : Tile (front/back):

Motor:

Spindle motor/max torque: KVA rating: Coolant pump (optional) Lubrication pump: Power requirement: 10" x 54" 36.37" 15.75" 5" 16" 3.375" (86 mm) 0.75"-16.75" (20–426 mm) 704 lb R8 70 to 4200 rpm with Hi/Lo gear Timing Belt 6.875" to 27.875" (175-707 mm) 19" (483 mm)

90 degree 45 degree

3HP (Std.) 4KVA, 15amps 1/8 Hp one shot 4 KVA, 3 Phase 208-230 voltage



ATRUMP MACHINERY, INC.

670 Union Ave. Pomona, CA 91768 Tel: 909-623-6887 Fax: (909) 623-2287 Toll Free Tel: 877-4 ATRUMP

URL:www.atrump.com. e-mail:atrump@atrump.com

Length X Width X Height (LXWXH): Net Weight: 102" x 77" x 84" 2,900 lbs.

MODEL	SPINDLE	Travel X/Y/Z	Tool	Table	SPINDLE	READOUT	FOB CA
			Change	Feed	MOTOR		
3VHG	R8	36.37x15.75x 16	Manual	Align (X)	2.2Kw(3HP)	Sino	\$ 8,305.00

STANDARD ACCESSORIES:

Tools & box	Align X-axis power feed	Sino 2-axis digital readout system
Leveling bolts & plate	Draw bar	Halogen work light
Way cover	One shot lube system	
Operation manual	R8 collect holder	

Additional Accessories information:

Power requirement	4 KVA 3 phase 208V/230Vmax		
Air requirement	With opt. power draw bar 90 - 100 psi		
Type of oil for Way oil / pneumatic oil	Mobil Vectra #2 / Air tool oil		
Coolant capacity	6 Gallons		

F.O.B.: Pomona, CA. 91768

DELIVERY: Please check with Atrump's Sales Team

STANDARD TERMS OF PAYMENT: 20% down-payment, balanced due on machine delivery **TAXES:** Federal, State, Local Taxes are the responsibility of Purchaser.

VALIDITY: This proposal is valid for 30 days.

WARRANTY: One-year limited warranty for any defects in material or workmanship of machine tool and factory installed components. Visit <u>www.atrump.com/policy</u> for full warranty details & contract.

** WE RESERVE THE RIGHT TO CHANGE DESIGN, COLOR, SPECIFICATIONS, OR PRICE WITHOUT NOTICE **